


Part No: MB-098-13




Mercedes Benz

Sprinter W907 06/2018 >> Sprinter W910 06/2018 >>

For models with and without trailer preparation!

Electric wiring kit for towbars / 13-pin / 12 Volt / ISO 11446 Fitting instructions





IMPORTANT!

This electric kit has to be installed by a professional workshop or a suitable qualified person.

The installation instructions must have been read and fully understood before the start of any installation. Please contact your wiring kit provider or the hotline shown in the footer should you need assistance!

Make sure the vehicle is approved/homologated by the manufacturer to tow a trailer!

Also please check that there is a definite compatibility between this vehicle and the electric kit!

Following the installation of the electric kit, the fitting instructions should be kept together with the vehicle service document and vehicle handbook. The fitting instructions contain important information relating to the use and function of the towing kit as well as for any diagnostic or activation process, that might have to be repeated in the future (e.g. after the performance of a vehicle software update).

All warranty claims will be forfeited if the electric kit or components contained therein are used incorrectly or modified. If a towing socket adaptor has been used to connect to the trailer or bike rack, this must be removed from the trailer socket once the trailer or bike rack has been disconnected.

If the trailer or bike rack is not equipped with a rear fog lamp, depending on the towing vehicle type, the correct function of the towing kit cannot be guaranteed. In such cases, a rear fog lamp should be retro fitted.

This towing electric kit will not be covered under warranty if any technical or electrical modifications or software updates have been performed by the vehicle manufacturer after the initial commissioning of the kit. That applies especially to modifications or updates which may cause malfunctions in the trailer socket or any other part of the trailer electrical equipment!

Depending on the type of trailer module used in this electric kit, diagnostic interrogation with the vehicle's electrical system may be limited or will not function. The error memory inside the trailer module may not be able to be accessed by vehicle manufacturers diagnostic system.

Error logs relating to the trailer electrical equipment, that may be generated in the vehicle manufacturers diagnostic system as a result of a test procedure, may be due to the incorrect installation of the towing electric kit or the false activation of the trailer module.

We always recommend whenever possible, the following troubleshooting process:

- → An analysis of the vehicle's error memory and possibly clearing of all faults before the start of the installation!
- Try disconnecting the trailer module from the towing harness and re-start the fault clearing process!
- → If in doubt, limit the time for troubleshooting to a max of 0,5 hours and call our Technical Support Team!

Please follow our instructions carefully and always test the towing electrics using a true lighting board or a specifically designed bulb tester. If an LED tester is used, ensure it is equipped with correct load resistors or malfunctions will occur!


This instruction is subject to changes and we reserve the right to make changes to design, colour etc.

All of the data and illustrations may not be an exact representation but the text contained in this instruction must be observed!

1/29

Right Connections UK Ltd Unit 503 Queensway Business Park TELFORD TF1 7UL UK

SALES: +44 (0)1952 608750 - Option 1 TECHNICAL: +44 (0)1952 608750 - Option 2 Web: www.rightconnections.co.uk
Email: reception@rightconnect.co.uk





SYMBOL EXPLANATION

-\\\\\\\-	Left (58-L) respectively Right (58-R) tail light						
54 (STOP)	Stop light (54) / high mounted, third stop light (54)						
__L	Turn signal indicator left						
R 🖒	Turn signal indicator right						
0#	Rear fog light(s)						
Reverse 0=	Reversing light(s)						
30+ •	Permanent power supply / 13pin socket, chamber 9						
15+ •	Charging wire for trailer battery / 13pin socket, chamber 10						
	Trailer / trailer recognition						
B+/30	Permanent current power supply						
<u></u>	Ground or Earth (31)						
$\overline{}$	Ground connection battery terminal lug						
•	Positive connection battery terminal lug						

(12V)	Cigarette lighter / accessory socket						
	Loudspeaker / buzzer						
	Park Distance Control						
-/-	Switch / source of function						
→	Connect together						
+	Disconnect						
4	Look at / See further information						
	Look carefully at selected area						
\bigvee	Present / Occupied / OK						
\mathbb{X}	Not present / Not occupied / Not OK						
D ((((Acoustic indication						
\triangle	Attention / important advice						
20 Amp.	Fuse / fuse capacity 20 Ampère						

TOOLS





ATTENTION!

The vehicle's cooling capacity may have to be increased when retrofitting a trailer coupling! You must observe the manufacturer's instructions!!



Note: It may be necessary to check if this vehicle has a stored radio code before disconnecting the battery!




ATTENTION!


In order to avoid mal-functions and damage to the vehicle's electrical system the earth terminal **must be disconnected** from the vehicle's battery **before starting work!**


Both the trailer module and the vehicle's control unit for the electrical system can be damaged during work on the data bus connections if the battery is not disconnected!


1


Please pay attention to the manufacturer's instructions when disconnecting and reconnecting the vehicle's battery!

























Vehicle with and without trailer preparation.


SOCKET CONNECTION


DIN/ISO	ļ	()≢	<u></u> -1-8	R□	-\̈́\.	STOP		Reverse 05	30+	15+	≟10		≟ 9
11446	1/L	2	3/31	4/R	5/58-R	6/54	7/58-L	8	9	10	11	12	13
Pmax	21W	21W		21W	52W	3x21W	52W	21W	240W	180W			
Colour	Yellow	Blue	White	Green	Brown	Red	Black	Pink	Orange	Grey	White/ Black	ı	White/ Red


11























































16/29





























Vehicle without trailer preparation.


| Mod - B+30 | Red Blue Ch. 10 | Pin 9- B+30 | Close secondary lock completely! | Red Blue Ch. 11 | Red Blue Ch. 10 | Red Blue Ch. 11 | Red Blue Ch. 10 |


41



















All Models



50

All Models

Set up trailer operation



General

After the installation of the electric kit, the obligatory trailer lighting, Towing vehicle and trailer stabilisation, as well as the trailer indicator control which is statutory in a several countries are guaranteed without having to make any connections on the vehicle!

NOTE:

In order for the rear fog light to cut-o automatically on the towing vehicle whilst a trailer/bike rack has been connected, diagnostic programming of the extended trailer functions together with optional assistance systems must be performed. Please proceed with the coding as follows:

Step 1:

Supplement optional extras via "Input for retrofit and conversions":

Add special equipment codes:

- + Q10 cross member for trailer hitch (trailer load up to 2t)
- + Q22 ball head fixed
- + **Q50** ball head removable
- + QA0 trailer hitch screwed for 2,8t trailer load
- + QA7 trailer hitch for increased trailer load 3.5t
- + QA8 trailer hitch fixed for increased hitch load (2.8t / 3.0t GVWR)
- + **E40** trailer socket 7 pin
- + **E43** trailer socket 13 pin

Remove existing optional extras code E57 (electrics for trailer socket)

Step 2:

- 1. Connect STAR DIAGNOSIS to car
- 2. Start program
- 3. Click "Controllers View"
- 4. code installed control units as follows:
- a. Click e.g. **"EZS"** (Ignition)
- b. Click "Adjust"
- c. On the left side:
- click updating SCN encoding
- d. Go online a wait a few seconds
- 5. Perform the operation with all the control units listed below:
- "EZS" (Ignition)
- "SAM" (Signal detection- and control modul).
- "combined instrument"
- "ESP" (Electronic Stability Program)
- "CPC" (Control Unit "Powertrain")


if fitted:


- "AUDIO" (car radio)
- "PTS" (Parktronic)
- "reversing camera"


► Coding finished

51

27/29







28/29

